


## Miniature Shaker KM 2



### Description

The orbital shaker KM 2 has a shaking platform of 200 x 295 mm which can be loaded with 2 kg. The stroke is 20 mm and the shaking speed between 5 and 220 rpm.

### Basic Equipment

Basic device incl. basic platform and rubber mat

### Loading Capacity

Erlenmeyer flasks 100 ml 9 pieces

Erlenmeyer flasks 500 ml 2 pieces

You will find further loading possibilities [here](#)

## Details

<b>Motion:</b>	orbital
<b>Shaking platform:</b>	200 x 295 mm
<b>Max. load:</b>	2 kg
<b>Shaking speed:</b>	5 - 220 rpm, in steps of 5
<b>Stroke:</b>	20 mm
<b>LED display:</b>	0 - 99 h 59 min / continuous
<b>Order No.:</b>	6113 000
<b>Accessory:</b>	Universaltablar KM Mini Universaltablar KM Spannleiste KM

## Technical specifications

<b>Electrical supply:</b>	100 - 240 V, 50 / 60 Hz
<b>Enclosure protection:</b>	IP 21
<b>Heat emission:</b>	approx. 0,5 - 2 W
<b>Ambient temperature:</b>	4°C to 45°C
<b>Relative humidity:</b>	~ 95 % (non-condensing)
<b>Dimensions (w x d x h):</b>	250 x 415 x 145 mm
<b>Weight:</b>	8,1 kg